

DWG.
NO.

BL2-FL

REV.
-

REV.

CAT. NO.

STUD HOLE

A

B

C

D

E

APPROX. WEIGHT (LB)

PENN-UNION DIELESS TOOLING (NO. OF CRIMPS)

STRIP LENGTH

METAL STAMP TO READ:
1. "CAT. NO."
2. PUC
3. 2-"STUD HOLE"
4. 

(E)


(A)


(B)

(C)

(D)

(STUD HOLE)





NOTES:
1. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
2. SEE INSTALLATION SHEET FOR WIRE SIZE AND TOOLING RECOMMENDATIONS
3. TIN-PLATED TO INHIBIT CORROSION
4. RATED FOR COPPER CONDUCTORS ONLY
5. BEVELED ENTRY FOR EASY CABLE INSERTION
6. CONNECTORS ARE SUITABLE FOR VOLTAGES UP TO 35 KV
7. FOR APPLICATIONS GREATER THAN 2000 VOLTS, CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS
8. CONNECTORS ARE UL LISTED PER UL486A-B FOR POWER APPLICATIONS UP TO 90°C

RoHS

COMPLIANT

NO.

ECN

DATE

REVISIONS

SEE TABLE

CAT. NO.

QTY.

PT.

NAME OR DESCRIPTION

COPPER BATTERY LUG
for
2 AWG COPPER CONDUCTORS

REF. DWG'S: 5H13-96920H:\5H13\BL2FL



PennUnion™

229 WATERFORD STREET
EDINBORO, PA 16412 USA

DRAWN BY: DTDATE: 8/15/2023CHK'D: MES

SCALE: 3:1INTERPRET PER ASME Y14.5-2009FILE: 5H13

SIZE: B



DWG.
NO.

BL2-FL

REV.
-

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO PENN-UNION CO. LLC. IT IS SUBMITTED IN CONFIDENCE AND IS TO BE USED SOLELY FOR THE PURPOSE FOR WHICH IT IS FURNISHED AND MUST BE RETURNED UPON REQUEST. THIS DOCUMENT AND SUCH INFORMATION IS NOT TO BE REPRODUCED, TRANSMITTED, DISCLOSED, OR USED OTHERWISE IN WHOLE OR IN PART WITHOUT THE EXPRESS CONSENT OF PENN-UNION CO. LLC.