



- NOTES:
1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
 2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
 3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
 4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
 5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
 6. INSTALLATION TORQUE: 120 IN•LB, STRIP LENGTH: .75
 7. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
 8. APPROX. WEIGHT: 0.033 LB



| | | |
|-----------|-------|-----------|
| 5 | 12187 | 6/8/2022 |
| 4 | 12060 | 3/30/2021 |
| 3 | 12055 | 3/26/2021 |
| 2 | 12050 | 3/24/2021 |
| 1 | 12038 | 2/22/2021 |
| NO. | ECN | DATE |
| REVISIONS | | |

| | | |
|-------------------------------|---|---------------------------------|
| 1 | 2 | SET SCREW, ALUMINUM, TIN PLATED |
| 1 | 1 | LUG BODY, ALUMINUM, TIN PLATED |
| QTY. | | PT. |
| NAME OR DESCRIPTION | | |
| ALUMINUM TERMINAL LUG | | |
| for | | |
| 2/0-#14 STR. | | |
| REF. DWG'S: 5J03-96607 | | H:\5J03\96607_C |
| DRAWN BY: QJB | | DATE: 4/24/2023 |
| SCALE: 2:1 | | CHK'D: NAK |
| INTERPRET PER ASME Y14.5-2009 | | FILE: 5J03 |
| SIZE: B | | DWG. NO. |
| 229 WATERFORD STREET | | LA-2/0 |
| EDINBORO, PA 16412 USA | | REV. 5 |